

RCI 2009-2014 F-150

Transfer-Case Skid Plate Installation

1. If purchased in combination with transmission skid plate, install transmission plate first.
2. Install all five speed clips into square openings in the chassis. Front three will already be installed if mounted in conjunction with transmission skid plate.
3. Loosen rear three bolts of the transmission skid plate about halfway, (allow plate to drop while bolts are loosened) until about 3/8" of bolt thread is visible between the truck chassis and plate.
4. If not installing in conjunction with transmission plate, install front three 30mm bolts leaving approximately 3/8" of thread visible.
5. Carefully lift transfer case skid plate into position, using a second person if necessary. Align notches at front of skid plate with the three previously installed bolts and slide plate in. If being used with transmission skid plate, slide plate in between transmission skid plate and chassis.
6. Install remaining two 30mm bolts securing skid plate on driver side frame rail.
7. Adjust skid plate if necessary then fully tighten all five bolts.

Included Hardware Kit

A.	M8 x 30mm Hex Bolt*	2 ea.
B.	M8 speed clips*	2 ea.
C.	5/16" Washers*	2 ea.
	*5 each If skid plate is purchased independently (without transmission skid)	



Enjoy the new protection!!!

Disclaimer: The products sold by RCI Metalworks are intended for off-road use only, should not be modified, and are for use only on the vehicle(s) specifically stated. RCI Metalworks makes no warranties express or implied, including of fitness for a particular purpose or merchantability. RCI Metalworks will not be liable for any damages arising out of the use or misuse of its products. It is the customers' responsibility to ensure the products are safely and properly attached to the vehicle, and all products should be installed by trained professionals. We strive to maintain extremely high quality standards; however, all RCI Metalworks products are individually handcrafted, may vary slightly, and may contain minor imperfections. Due to the nature of raw aluminum, the material may have minor scratches and other blemishes caused by the manufacturing process, especially on the back side of product. RCI Metalworks is constantly seeking to improve its products and reserves the right to make changes to any product.