## 2007-19 Tundra RCI A-Arm Skid Plate Installation

- 1. Lift front of vehicle with jacks or ramps, and safely secure it if extra working room is necessary.
- 2. Locate mounting holes on A-arms, prior to lifting into position.
- 3. Lift A-arm skid plate into position, and insert carriage bolt <u>A</u> through front hole. Install washer and locknut on top of A-arm, leaving loose enough to adjust plate.
- 4. Install carriage bolt  $\underline{\mathbf{A}}$  through the rear hole, with washer and locknut on top of A-arm.
- 5. Adjust as necessary, then install remaining carriage bolt <u>A</u> through hole closest to tire, with washer and locknut on top of A-arm.
- 6. Adjust plate as necessary then fully tighten all bolts and locknuts. Make sure to keep skid plates pushed back as tight as possible to front edge of control arm in order to maximize clearance between wheel when turning.
- 7. Repeat steps for opposite A-arm skid plate.
- 8. With vehicle on the ground, turn wheels both directions all the way to the locks and make sure there is sufficient clearance to the wheels. About ½" is typical on a stock truck but larger wheels, wheel spacers, or different offset wheels could change (usually increase) this clearance.

## Enjoy the new protection!!!

## **Included Hardware Kit**

A.	3/8" x 3.75" Carriage Bolt	6 ea.
В.	3/8" Nylon Lock-nut	6 ea.
C.	3/8" Washer	6 ea.



Disclaimer: The products sold by RCI Metalworks are intended for off —road use only, should not be modified, and are for use only on the vehicle(s) specifically stated. RCI Metalworks makes no warranties express or implied, including of fitness for a particular purpose or merchantability. RCI Metalworks will not be liable for any damages arising out of the use or misuse of its products. It is the customers' responsibility to ensure the products are safely and properly attached to the vehicle, and all products should be installed by trained professionals. We strive to maintain extremely high quality standards; however, all RCI Metalworks products are individually handcrafted, may vary slightly, and may contain minor imperfections. Due to the nature of raw aluminum, the material may have minor scratches and other blemishes caused by the manufacturing process, especially on the back side of product. RCI Metalworks is constantly seeking to improve its products and reserves the right to make changes to any product.